

Specifications

STANDARD CONSTRUCTION

- Bulkhead 14 gauge galvanized steel
- Compartment Bottoms 16 gauge galvanized steel
- Compartment Tops 14 gauge galvanized steel one-piece seamless design with loadspace inside centers
- Crossmember – Front 7 gauge formed steel
- Crossmember – Inter 12 gauge formed steel
- Crossmember – Rear 7 gauge formed steel
- Doors 20 gauge galvanized steel double panel with hat section reinforcement
- End Panels – Front 14 gauge galvanized steel with seamless weatherstrip
- End Panels – Rear 14 gauge galvanized steel seamless
- Fender Panels 14 gauge galvanized steel
- Floor 12 gauge treadplate steel
- Intermediate Panels 16 gauge galvanized steel
- Loadspace Inside Centers 14 gauge galvanized steel one-piece seamless design with compartment tops
- Longitudinals (floor) 11 gauge formed steel
- Shelving 16 gauge high-spangle galvanized steel – 250# capacity
- Tailgate 16 gauge galvanized steel double panel formed
- Steel is A-40 two-sided zinc-coated galvanized (.40 ounces of zinc coating per square foot of steel).
- Body construction is welded. Body surfaces are flush with unexposed edges for rust-resistance.



Note: Tailgate is now pick-up style.



NEW! Pick-up style tailgate.

STANDARD FEATURES / EQUIPMENT

- Vinyl-coated aircraft cables on horizontal doors.
- Spring-loaded vertical door holders (double spring to hold door in open position).
- Doors have beveled edges for improved weather seal.
- Automotive bulb-type door seal (factory installed).
- Drip rail runs the full length of the body and provides extra protection against water leakage.
- Fender is die-stamped with radius wheel opening.
- Door hinge rod is cadmium-plated with zinc-cast hinge blocks and nylon bushings.
- Lock cylinders are keyed alike with double-bitted keys.
- Body mounting kit (bodies have universal understructures).
- One-piece seamless compartment top and loadspace inside center.
- Prime paint is a high-grade automotive type. Bodies are cleaned with a high-temperature, high-pressure chemical solution prior to prime painting.
- Rotary door latches with stainless steel paddle handles and galvanized steel pans. Latches are rivet-on for ease of removal for repair or replacement.
- Shuttle cutout (7" x 16") between horizontal and rear vertical compartments provides extended storage from the horizontal compartment into the rear vertical compartment (not available on top pak models).
- Striker is adjustable, bolt-on. Steel striker support bracket is welded to body panel.
- **Tailgate** – Two point slam-locking, removable and features locking rotary latch and anti-rack/rattle hardware.
- Undercoating on underside of floor and wheel wells.
- Vertical weatherstrip shields door hinges and hinge rod and provides extra protection against water leakage. Weatherstrip is seamless design on front end panels.
- **STAHL**'s exclusive 5-year "No Rust, No Bust" warranty.

Continues on reverse side.

STANDARD SHELVING PACKAGE

“V” Side Compartmentation (full-height front vertical(s), short horizontal, full-height rear vertical)

COMPARTMENT	BODY SIZE	COMPT. WIDTH	CURBSIDE	STREETSIDE
	96" 108" 132" 156"	26" 32" 24" 24"	One (1) adjustable material tray with dividers and one (1) adjustable plain shelf	One (1) adjustable material tray with dividers and one (1) adjustable plain shelf
Second Vertical	132" 156"	32" 24"	Two (2) adjustable plain shelves	Two (2) adjustable plain shelves
Third Vertical	156"	32"	Two (2) adjustable plain shelves	Two (2) adjustable plain shelves
Horizontal	All	50"	One (1) full-width adjustable (bolt-in) material tray with dividers	Open
Rear Vertical	96" 108" 132" 156"	20" 26" 26" 26"	One (1) adjustable plain shelf	One (1) adjustable plain shelf

“C” Side Compartmentation (full-height front vertical(s), long horizontal, short rear vertical)

COMPARTMENT	BODY SIZE	COMPT. WIDTH	CURBSIDE	STREETSIDE
Front Vertical	96" 108" 132" 156"	26" 32" 24" 24"	One (1) adjustable material tray with dividers and one (1) adjustable plain shelf	One (1) adjustable material tray with dividers and one (1) adjustable plain shelf
Second Vertical	132" 156"	32" 24"	Two (2) adjustable plain shelves	Two (2) adjustable plain shelves
Third Vertical	156"	32"	Two (2) adjustable plain shelves	Two (2) adjustable plain shelves
Horizontal	96" 108" 132" 156"	70" 76" 76" 76"	One (1) adjustable (bolt-in) material tray with dividers	Open
Rear Vertical	96" 108" 132" 156"	20" 26" 26" 26"	Open	Open

DIMENSIONAL SPECIFICATIONS

Standard Height Models ("V")

DESCRIPTION	96S	96D	108S	108D	108D	132D	132D	156D	156D
Floor width	48 1/2"	54"	48 1/2"	48 1/2"	54"	48 1/2"	54"	48 1/2"	54"
Cab-to-axle	56"	56"	60"	60"	60"	84"	84"	108"	108"
Body length	96"	96"	108"	108"	108"	132"	132"	156"	156"
Front vertical width	26"	26"	32"	32"	32"	24"	24"	24"	24"
Clear door opening	24 5/16"	24 5/16"	30 5/16"	30 5/16"	30 5/16"	21 5/16"	21 5/16"	21 5/16"	21 5/16"
Second vertical width	n/a	n/a	n/a	n/a	n/a	32"	32"	24"	24"
Clear door opening	n/a	n/a	n/a	n/a	n/a	30 5/16"	30 5/16"	21 5/16"	21 5/16"
Third vertical width	n/a	n/a	n/a	n/a	n/a	n/a	n/a	32"	32"
Clear door opening	n/a	n/a	n/a	n/a	n/a	n/a	n/a	30 5/16"	30 5/16"
Horizontal width	50"	50"	50"	50"	50"	50"	50"	50"	50"
Clear door opening	45 5/8"	45 5/8"	45 5/8"	45 5/8"	45 5/8"	45 5/8"	45 5/8"	45 5/8"	45 5/8"
Rear vertical width	20"	20"	26"	26"	26"	26"	26"	26"	26"
Clear door opening	18 5/16"	18 5/16"	24 5/16"	24 5/16"	24 5/16"	24 5/16"	24 5/16"	24 5/16"	24 5/16"
Overall body width	78 1/2"	96"	78 1/2"	90 1/2"	96"	90 1/2"	96"	90 1/2"	96"
Compartment depth	15"	21"	15"	21"	21"	21"	21"	21"	21"
Vertical compartment height	39"	39"	39"	39"	39"	39"	39"	39"	39"
Clear door opening	34 1/4"	34 1/4"	34 1/4"	34 1/4"	34 1/4"	34 1/4"	34 1/4"	34 1/4"	34 1/4"
Horizontal compartment height	18"	18"	18"	18"	18"	18"	18"	18"	18"
Clear door opening	15 3/16"	15 3/16"	15 1/4"	15 1/4"	15 1/4"	15 1/4"	15 1/4"	15 1/4"	15 1/4"
Floor-to-compartment top height	26"	26"	26"	26"	26"	26"	26"	26"	26"
Tailgate height above floor	10"	10"	10"	10"	10"	10"	10"	10"	10"

Low Profile Models ("V")

DESCRIPTION	96SL	96DL	108SL	108DL	108DL
Floor width	48 1/2"	54"	48 1/2"	48 1/2"	54"
Cab-to-axle	56"	56"	60"	60"	60"
Body length	96"	96"	108"	108"	108"
First vertical width	26"	26"	32"	32"	32"
Clear door opening	24 5/16"	24 5/16"	30 5/16"	30 5/16"	30 5/16"
Second vertical width	n/a	n/a	n/a	n/a	n/a
Clear door opening	n/a	n/a	n/a	n/a	n/a
Third vertical width	n/a	n/a	n/a	n/a	n/a
Clear door opening	n/a	n/a	n/a	n/a	n/a
Horizontal width	50"	50"	50"	50"	50"
Clear door opening	45 5/8"	45 5/8"	45 5/8"	45 5/8"	45 5/8"
Rear vertical width	20"	20"	26"	26"	26"
Clear door opening	18 5/16"	18 5/16"	24 5/16"	24 5/16"	24 5/16"
Overall body width	78 1/2"	96"	78 1/2"	90 1/2"	96"
Compartment depth	15"	21"	15"	21"	21"
Vertical compartment height	36"	36"	36"	36"	36"
Clear door opening	31 1/4"	31 1/4"	31 1/4"	31 1/4"	31 1/4"
Horizontal compartment height	15"	15"	15"	15"	15"
Clear door opening	12 3/16"	12 3/16"	12 3/16"	12 3/16"	12 3/16"
Floor-to-compartment top height	23"	23"	23"	23"	23"
Tailgate height above floor	10"	10"	10"	10"	10"

OPTIONAL EQUIPMENT

- Aerial Reinforcement
- Bar Lock
- Bumper (treadplate, straight, non-lighted)
- Bumper (treadplate, straight, lighted)
- Bumper (treadplate, recessed, non-lighted)
- Bumper (treadplate, recessed, lighted)
- Bumper (treadplate, recessed, GMT lighted)
- Bumper (gripstrut, recessed, non-lighted)
- Crane Reinforcement
- Dome Light
- Drawer
- High Roof
- Hook
- Hot Stick Box
- Ladder Rack
- Light Kit
- Louver
- Low Sliding Roof
- Mounting Kit
- Off-Road Mounting Kit
- Paint and Installation
- Pipe Carrier
- Pull-Out Tray
- Rope Rail
- Shelf
- Tank Compartment
- Thru Shelf
- Tie-Down Ring
- Tire Carrier
- Top Pak (add-on)
- Transverse Compartment
- Tray
- Treadplate Overlay

Due to constant product evaluations and improvements, specifications and options are subject to change without notice.

