

Specifications

STANDARD CONSTRUCTION

- Bulkhead 14 gauge galvanized steel
- Compartment bottoms ... 14 gauge galvanized steel
- Compartment Tops/Inside Centers 14 gauge galvanized steel (one-piece seamless design with loadspace inside centers)
- Crossmember – front 7 gauge formed (one front crossmember)
- Crossmember – intermed. 7 gauge formed
- Crossmember – rear 7 gauge formed (one rear crossmember)
- Doors 18 gauge galvanized steel outer panel and 20 gauge galvanized steel inner panel with 20 gauge galvanized steel hat section reinforcement and center hinge design
- End panels 14 gauge galvanized steel (front and rear)
- Fender panels 14 gauge galvanized steel with rubber fenderettes
- Floor 12 gauge treadplate steel
- Intermediate panels 14 gauge galvanized steel
- Kick plate 10 gauge galvanized full-width
- Shelving 16 gauge high-spangle galvanized steel (250# capacity)
- Tailgate 16 gauge galvanized (double panel, formed construction)
- Body construction is welded.
- Flush outside body surfaces with unexposed edges for rust-resistance

STANDARD FEATURES / EQUIPMENT

- Vinyl-coated aircraft cables on horizontal doors.
- Spring-loaded vertical door holders (double spring to hold door in open position).
- Doors have beveled edges for improved weather seal.
- Automotive bulb-type door seal (factory installed).
- Drip rail runs the full length of the body and provides extra protection against water leakage.
- Fender has radius opening with rubber fenderettes.
- Door hinge rod is full-length cadmium-plated with rivet-on zinc-cast hinge blocks and nylon bushings.
- Lock cylinders are keyed alike with double-bitted keys.
- Body mounting kit (bodies have universal understructures).
- One-piece seamless compartment top and loadspace inside center for 108" and 132" long bodies.
- Rear vertical compartment doors are rearward opening and open a full 90°.
- Rotary door latches with stainless steel paddle handles and galvanized steel pans. Latches are rivet-on for ease of removal for repair or replacement.
- Shuttle cutout (11" x 16") between the horizontal and rear vertical compartments provides extended storage from the horizontal compartment into the rear vertical compartment.
- Striker is adjustable, weld-on.
- **Tailgate** – Two point slam-locking, removable and features locking rotary latch and anti-rack/rattle hardware.
- Vertical weatherstrip shields door hinges and hinge rod and provides extra protection against water leakage. Weatherstrip is seamless design on front end panels.

STANDARD FEATURES / EQUIPMENT continued.

- Vertical compartment bottoms do not have any offsets. This provides more useable space, allows full-height adjustment of material trays and shelves, and enables full-height drawer packages.
- Weld-on grab handles (one curbside rear and one streetside rear) for loadspace access.

- **Prime paint** is a high-grade automotive type. Bodies are cleaned with a high-temperature, high-pressure chemical solution prior to prime painting.
- **Undercoating** on underside of floor and wheel wells.
- **STAHL**'s exclusive 5-year "No Rust, No Bust" **warranty**.

COMPARTMENTATION

Curbside

Front verticals	Two adjustable material trays with adjustable dividers
Horizontal	One full-width adjustable (bolt-in) material tray with adjustable dividers
Rear verticals	One adjustable material tray with adjustable dividers

Streetside

Front verticals	Two adjustable material trays with adjustable dividers
Horizontal	Open
Rear verticals	One adjustable material tray with adjustable dividers

DIMENSIONAL SPECIFICATIONS

Compartment Depth	21"
Floor Width	54"
Overall Body Width	96"
Front Vertical Length	Varies depending on body size
Horizontal Length	52"
• Clear Door Opening	47.25"
Rear Vertical Length	Varies depending on body size
Vertical Compartment Height	48"
• Clear Door Opening	43.13"
Horizontal Compartment Height	21"
• Clear Door Opening	18"
Floor to Compartment Top Height	29"
Floor to Compartment Bottom	19"
Tailgate Height Above Floor	9.5"

Due to constant product evaluations and improvements, specifications and options are subject to change without notice.

