

Specifications

MODEL 30 UNDERBODY TOOLBOX

STANDARD CONSTRUCTION

- Back panel 14 gauge galvanized steel
- Bottom panel 14 gauge galvanized steel
- End panels 14 gauge galvanized steel
- Top panel 14 gauge galvanized steel
- Doors 20 gauge galvanized steel double panels with 20 gauge hat channel reinforcement
- Steel is A-40 two-sided zinc-coated galvanized (.40 ounces of zinc coating per square foot of steel).
- Flush outside box surfaces with unexposed edges for superior rust resistance.



STANDARD FEATURES / EQUIPMENT

- Drop down door(s).
- Keyed alike lock cylinders with double bit keys.
- Automotive style door seal double seals the entire perimeter of the door.
- Doors are double panel construction.
- Slam action latches with stainless steel paddle handles and galvanized pans.
- Slam latches (rivet on) on all doors.
- Continuous plated hinge rod formed into door.
- Integral drip edge protects contents of box when opening the door.
- Primer is a high-grade automotive type. Toolboxes are cleaned with a high temperature, high-pressure chemical solution prior to prime painting.
- Boxes shipped loose are in prime paint. Boxes can be shipped on a route trailer with bodies or via motor freight.
- **STAHL**'s 3-year limited warranty.

DIMENSIONAL SPECIFICATIONS

Model 30 Underbody Toolbox

MODEL NUMBER	30-20	30-24	30-30	30-36	30-48	30-60	30-72
Number of doors	1	1	1	1	1	1	1
Number of handles per door	1	1	1	1	1	2	2
Width	20"	24"	30"	36"	48"	60"	72"
Height	18"	18"	18"	18"	18"	18"	18"
Depth	18"	18"	18"	18"	18"	18"	18"
Approximate weight	58#	65#	75#	85#	120#	134#	161#

NOTE: Model 30 boxes are made to be bolted or welded to the underside of a flatbed.

Continues on reverse side

Specifications

MODEL 50 SIDE TOOLBOX

STANDARD CONSTRUCTION

- Back panel 16 gauge galvanized steel
- Bottom panel 16 gauge galvanized steel
- End panels 16 gauge galvanized steel
- Top panel 16 gauge galvanized steel
- Doors 20 gauge galvanized steel outer panel and 20 gauge galvanized steel inner panel
- Steel is A-40 two-sided zinc-coated galvanized (.40 ounces of zinc coating per square foot of steel).
- Flush outside box surfaces with unexposed edges for superior rust resistance.



STANDARD FEATURES / EQUIPMENT

- Drop down door(s).
- Automotive style door seal double seals the entire perimeter of the door.
- Doors are double panel construction.
- Lock cylinders are keyed alike with double-bitted keys.
- Slam action latches with stainless steel paddle handles and galvanized pans. Latches are bolt-on for ease of removal for repair or replacement.
- Continuous plated hinge rod formed into door.
- Door chains.
- Integral drip edge protects contents of box when opening the door.
- Primer is a high-grade automotive type. Toolboxes are cleaned with a high temperature, high-pressure chemical solution prior to prime painting.
- Mounting kit is included.
- Boxes shipped loose are in prime paint. Boxes can be shipped on a route trailer with bodies or via motor freight.
- **STAHL**'s 3-year limited warranty.

DIMENSIONAL SPECIFICATIONS

Model 50 Side Toolbox

MODEL NUMBER	50-48	50-60	50-72	50-90	50-96	50-102	50-108
Number of doors	1	1	1	2	2	2	2
Number of handles per door	1	2	2	1	1	1	1
Length	48"	60"	72"	90"	96"	102"	108"
Height	15"	15"	15"	15"	15"	15"	15"
Depth	12 -3/4"	12 -3/4"	12 -3/4"	12 -3/4"	12 -3/4"	12 -3/4"	12 -3/4"
Approximate weight	85#	100#	115#	120#	135#	143#	152#

NOTE: Model 50 boxes are made to install in a pickup bed.

Due to constant product evaluations and improvements, specifications and options are subject to change without notice.

